

Amendments to the Claims:

This listing of claims replaces all prior versions and listings of claims in the application:

1. (Original) A method for determining whether a call forward busy service is enabled on a telephone line, the method comprising:

- placing a first test call across a network to the telephone line;
- receiving first signaling data through the network in response to the first test call;
- evaluating the first signaling data to determine whether the first test call is inspiring a ringing condition;
- placing a second test call across the network conditioned on whether the first signaling data indicates that the first test call is determined to be inspiring a ringing condition, the second test call being placed while the first test call remains inspiring ringing;
- receiving second signaling data through the network in response to the second test call;
- evaluating the second signaling data to determine whether the second test call is inspiring a ringing condition;
- concluding whether a call forward busy service is enabled on the telephone line based on whether the second test call is determined to be inspiring a ringing condition.

2. (Original) The method of claim 1, wherein the telephone network comprises a circuit-switched voice network.

3. (Original) The method of claim 1, wherein the telephone network comprises a packet-switched data network.

4. (Original) The method of claim 1, wherein the duration of the first test call and the duration of the second test call are such that a ringing condition is not inspired for more than 2 seconds when negligible delay is introduced by the network.

5. (Original) The method of claim 1, wherein the first test call is inspiring a ringing condition for less than 2 seconds when negligible delay is introduced by the network.
6. (Original) The method of claim 5, wherein the first test call and the second test call are simultaneously inspiring ringing for less than 2 seconds when negligible delay is introduced by the network.
7. (Original) A computer system configured to determine a call forward busy service enabled on a telephone line, the computer system comprising:
 - a telephony server configured to:
 - place a first test call across a network to the telephone line;
 - receive first signaling data through the network in response to the first test call;
 - evaluate the first signaling data to determine whether the first test call is inspiring a ringing condition;
 - place a second test call across the network conditioned on whether the first signaling data indicates that the first test call is determined to be inspiring a ringing condition, the second test call being placed while the first test call remains inspiring ringing;
 - receive second signaling data through the network in response to the second test call;
 - evaluate the second signaling data to determine whether the second test call is inspiring a ringing condition;
 - conclude whether a call forward busy service is enabled on the telephone line based on whether the second test call is determined to be inspiring of a ringing condition.
8. (Original) The computer system of claim 7, wherein the telephone network comprises a circuit-switched voice network.
9. (Original) The computer system of claim 7, wherein the telephone network comprises a packet-switched data network.

10. (Original) The computer system of claim 7, wherein the telephony server is configured to limit the duration of the first test call and the duration of the second test call such that a ringing condition is not inspired for more than 2 seconds when negligible delay is introduced by the network.

11. (Original) The computer system of claim 7, wherein the telephony server is configured to limit the duration of the first test call such that the first test call is inspiring ringing for less than 2 seconds when negligible delay is introduced by the network.

12. (Original) The computer system of claim 11, wherein the telephony server is configured to limit the duration of the first test call and the duration of the second test call such that the first test call and the second test call are simultaneously inspiring ringing for less than 2 seconds when negligible delay is introduced by the network.

13. (Original) An apparatus for determining whether a call forward busy service is enabled on a telephone line, the apparatus comprising:

means for placing a first test call across a network to the telephone line;

means for receiving first signaling data through the network in response to the first test call;

means for evaluating the first signaling data to determine whether the first test call is inspiring a ringing condition;

means for placing a second test call across the network conditioned on whether the first signaling data indicates that the first test call is determined to be inspiring a ringing condition, the second test call being placed while the first test call remains inspiring ringing;

means for receiving second signaling data through the network in response to the second test call;

means for evaluating the second signaling data to determine whether the second test call is inspiring a ringing condition;

means for concluding whether a call forward busy service is enabled on the telephone line based on whether the second test call is determined to be inspiring of a ringing condition.

14. (Currently amended) A method for externally determining whether a voicemail service is enabled on a telephone line, the method comprising:

placing one or more test calls from a first entity across a network to the telephone line of a call recipient, wherein:

the duration that the test call or calls are inspiring ringing is such that a ringing condition does not last for more than 2 seconds when negligible delay is introduced by the network or

the duration that the test call or calls are inspiring ringing is less than 2 seconds when negligible delay is introduced by the network;

receiving signaling data through the network in response to the test calls; and

concluding whether a voicemail service is enabled on the telephone line based on the received signaling data,

wherein the first entity and the call recipient are different entities.

15. (Original) The method of claim 14, wherein concluding whether a voicemail service is enabled on the telephone line includes determining whether a call forward busy service is enabled on the telephone line.

16. (Original) The method of claim 15, wherein determining whether a call forward busy service is enabled on the telephone line includes evaluating the signaling data received in response to at least one of the test calls.

17. (Previously presented) A method for externally determining whether a voicemail service is enabled on a telephone line, the method comprising:

placing one or more test calls across a network to the telephone line;

receiving signaling data through the network in response to the test calls; and

concluding whether a voicemail service is enabled on the telephone line based on the received signaling data,

wherein placing one or more test calls includes:

placing a first test call;

determining whether the first test call is inspiring a ringing condition; and

placing a second test call conditioned on whether the signaling data indicates that the first test call is determined to be inspiring a ringing condition, the second test call being placed while the first test call remains inspiring ringing.

18. (Original) The method of claim 17, wherein receiving signaling data through the network in response to the test calls includes receiving first signaling data in response to the first test call and receiving second signaling data in response to the second test call, and wherein determining whether the first test call is inspiring a ringing condition includes evaluating the first signaling data.

19. (Original) The method of claim 18, wherein concluding whether a voicemail service is enabled on the telephone line includes determining whether a call forward busy service is enabled on the telephone line.

20. (Original) The method of claim 19, wherein determining whether a call forward busy service is enabled on the telephone line comprises determining that the first signaling data corresponds to the first test call inspiring a ringing condition, and determining that the second signaling data corresponds to the second test call inspiring a ringing condition.

21. (Original) The method of claim 14, wherein the telephone network comprises a circuit-switched voice network.

22. (Original) The method of claim 14, wherein the telephone network comprises a packet-switched data network.

23. (Original) The method of claim 14, wherein the duration that the test call or calls are inspiring ringing is such that a ringing condition does not last for more than 2 seconds when negligible delay is introduced by the network.

24. (Original) The method of claim 14, wherein the duration that the test call or calls are inspiring ringing is less than 2 seconds when negligible delay is introduced by the network.

25. (Previously presented) A method for externally determining whether a voicemail service is enabled on a telephone line, the method comprising:

- placing one or more test calls across a network to the telephone line;
- receiving signaling data through the network in response to the test calls; and
- concluding whether a voicemail service is enabled on the telephone line based on the received signaling data,

wherein a second test call is placed while a first test call is still inspiring ringing.

26. (Original) The method of claim 25, wherein the first test call and the second test call are simultaneously inspiring ringing for less than 2 seconds when negligible delay is introduced by the network.

27. (Currently amended) A computer system for externally determining whether a voicemail service is enabled on a telephone line, the computer system comprising:

a telephony server configured to:

- place one or more test calls across a network to the telephone line of a call recipient;
- receive signaling data through the network in response to the test calls; [[and]]
- conclude whether a voicemail service is enabled on the telephone line based on the received signaling data; and
- limit the duration that the test call or calls are inspiring ringing such that the ringing condition does not last for more than 2 seconds when negligible delay is

introduced by the network or limit the duration that the test call or calls are inspiring ringing to less than 2 seconds when negligible delay is introduced by the network,
wherein the telephony server and the call recipient are different entities.

28. (Original) The computer system of claim 27, wherein the telephony server is configured to conclude whether a voicemail service is enabled on the telephone line by determining whether a call forward busy service is enabled on the telephone line.

29. (Original) The computer system of claim 28, wherein the telephony server is configured to determine whether a call forward busy service is enabled on the telephone line by evaluating signaling data received in response to at least one of the test calls.

30. (Previously presented) A computer system for externally determining whether a voicemail service is enabled on a telephone line, the computer system comprising:

a telephony server configured to:

place one or more test calls across a network to the telephone line;

receive signaling data through the network in response to the test calls; and

conclude whether a voicemail service is enabled on the telephone line based on the received signaling data,

wherein the telephony server is configured to place one or more test calls by:

placing a first test call;

determining whether the first test call is inspiring a ringing condition; and

placing a second test call conditioned on whether the signaling data indicates that the first test call is determined to be inspiring a ringing condition, the second test call being placed while the first test call remains inspiring ringing.

31. (Original) The computer system of claim 30, wherein the telephony server is configured to receive signaling data through the network in response to the test calls by receiving first signaling data in response to the first test call and receiving second signaling data in response to

the second test call, wherein determining whether the first test call is inspiring a ringing condition includes evaluating the first signaling data.

32. (Original) The computer system of claim 31, wherein the telephony server is configured to conclude that a voicemail service is enabled on the telephone line by determining whether a call forward busy service is enabled on the telephone line.

33. (Original) The computer system of claim 32, wherein the telephony server is configured to determine whether a call forward busy service is enabled on the telephone line by determining that the first signaling data corresponds to the first test call inspiring ringing and determining that the second signaling data corresponds to the second test call inspiring ringing.

34. (Original) The computer system of claim 27, wherein the telephone network comprises a circuit-switched voice network.

35. (Original) The computer system of claim 27, wherein the telephone network comprises a packet-switched data network.

36. (Original) The computer system of claim 27, wherein the telephony server is configured to limit the duration that the test call or calls are inspiring ringing such that the ringing condition does not last for more than 2 seconds when negligible delay is introduced by the network.

37. (Original) The computer system of claim 27, wherein the telephony server is configured to limit the duration that the test call or calls are inspiring ringing to less than 2 seconds when negligible delay is introduced by the network.

38. (Previously presented) A computer system for externally determining whether a voicemail service is enabled on a telephone line, the computer system comprising:

a telephony server configured to:

place one or more test calls across a network to the telephone line;

receive signaling data through the network in response to the test calls; and
conclude whether a voicemail service is enabled on the telephone line based on
the received signaling data,
wherein the telephony server is configured to place a second test call while a first test call
is still inspiring ringing.

39. (Original) The computer system of claim 38, wherein the telephony server is configured
to limit the duration of the first test call and the duration of the second test call such that the first
test call and the second test call are simultaneously inspiring ringing for less than 2 seconds
when negligible delay is introduced by the network.

40. (Canceled)

41. (Previously presented) The method of claim 1, wherein placing a first test call across a
network to the telephone line comprises placing a first test call from a first entity across a
network to a telephone line of a call recipient, wherein the call recipient and the first entity are
different entities.

42. (Previously presented) The method of claim 7, wherein the telephony server is configured
to place a first test call across a network by placing a first test call across a network to a
telephone line of a call recipient, wherein the telephony server and the call recipient are different
entities.